



# MOTOR OIL API: SN

## FULLY SYNTHETIC

Magic Plus API: SN fully synthetic engine oil is designed to help deliver outstanding engine protection in recent cars fitted with naturally aspirated or turbocharged, indirect or direct injection. It meets the requirements of the latest industry standards for "Full SAPS" passenger car lubricants and outperforms conventional oils. These oils are designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and excellent low-temperature performance.

### Features & Benefits:

- Quick cold-weather starting and fast protection helps extend engine life
- Outstanding thermal and oxidation stability
- Used for all high-performance gasoline engine cars equipped with direct-injection, multi-valve, and turbo-charged technologies.
- Formulated for optimum viscosity control the life of the oil.

### Applications:

Suitable for all type of fuels: leaded or unleaded Gasoline, Ethanol, LPG, Diesel and biofuels. Compatible for catalytic converters.

### Specifications, Approvals & Recommendations: (Meets / Exceeds)

SAE Grade	<b>0W-30</b>	<b>0W-40</b>	<b>5W-30</b>	<b>5W-40</b>	<b>10W-40</b>
API	SL/CF	SN/CF	SN*/SL/CF	SN/CF	SN/CF
ACEA	A3/B4	A3/B4	A3/B4	A3/B4	A3/B4
Volvo	95200356	-	-	-	-
Porsche	-	A40	-	A40	-
MB	226.5/229.3/22.95	226.5/229.3/22.95	226.5/229.3/22.95	226.5/229.3/22.95	226.5/229.3
Renault	RN0700/0710	RN0700/0710	RN0700/0710	RN0700/0710	RN0700/0710
VW	502 00 / 505 00	502 00 / 505 00	502 00 / 505 00	502 00 / 505 00	-
BMW	LL-01	LL-01	LL-01	LL-01	-
PSA	-	-	-	B71 2296	-
Ford	-	WSS-M2C-937-A	-	-	-

### Technical Data:

Parameters	ASTM	Unit	Typical Results				
			<b>0W-30</b>	<b>0W-40</b>	<b>5W-30</b>	<b>5W-40</b>	<b>10W-40</b>
Viscosity Grade			<b>0W-30</b>	<b>0W-40</b>	<b>5W-30</b>	<b>5W-40</b>	<b>10W-40</b>
Viscosity @ 104 °F / 40 °C	D-7042	cSt	66.69	87.5	68.4	91	102
Viscosity @ 212 °F / 100 °C	D-7042	cSt	11.84	14.9	11.6	15	15.1
Viscosity Index	D-2270		176	180	166	173	156
Density @ 60 °F / 15 °C	D-4052	g/cm <sup>3</sup>	0.846	0.845	0.850	0.851	0.875
Flash Point (min)	D-92	°C	230	230	232	230	232
Pour Point (min)	D-97	°C	-40	-42	-42	-42	-39
TBN	D-2896	mg KOH/g	10	10	10	10	10

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. For further Information on Safety Guidelines please refer to MSDS available on our website [magicplusoil.net](http://magicplusoil.net)

All statements, information, and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Magic Plus and its affiliates assume legal responsibility.