



ATF DEXRON VI

SYNTHETIC

Magic Plus ATF Dexron VI is a synthetic transmission fluid recommended for use in passenger cars and light trucks automatic transmissions that require a GM Dexron VI or earlier generation fluid. Transmissions include the following Aisin Warner models: AW TF-80SC / SD, AWF21, AF40-6, AM6, AW6A-El, TF81SC, AF21, GA6F21WA (Mini).

Features & Benefits:

- Outstanding friction durability for consistent shift performance for the life of the fluid.
- Excellent oxidation resistance and thermal stability
- Protects against sludge and varnish formation
- Protects against wear
- High shear stability
- Excellent low-temperature properties

Applications:

All automatic transmissions that require a GM Dexron VI or earlier generation transmission fluid. Hydraulic systems or industrial and mobile equipment operating over a wide temperature range.

Specifications, Approvals & Recommendations: (Meets / Exceeds)

- GENERAL MOTORS DEXRON II/III/IIII/VI
- JWS 3309, JWS 3324, T-IV, AW-1, NWS 9638
- AUDI/VW G-052-162-A1/A2
- BMW ETL-7045, 7045E, LA2634
- BMW ETL-8072B, 81 22 9 400 275
- CHRYSLER M1375.4
- FIAT (ALL VEHICLES) TYPO T-IV
- HONDA ACURA Z-1 PREMIUM, HONDAMATIC S
- HYUNDAI / KIA SP IV, HYUNDAI SPH-IV
- ISUZU BESCO ATF II, ATF III
- JAGUAR ATF 3403 M115, JLM 20238
- PORSCHE ATF 3403-M115
- VOITH 55.6635
- MAZDA ATF M III
- MITSUBISHI DIAMOND SP-IV
- MB ZF 4 HP20, 236.1/5/6/7/8/9/236.41
- PEUGEOT ZF 4 HP20
- TOYOTA TYPE T-III, T-IV, WS
- TOYOTA P/N 08886-02305/08886-81015
- ZF 5HP 18FL/19FL/24A
- ZF 5HP 30, TE-ML 09
- BMW P/N 833227542290
- CITROEN P/N PR 9980
- MERCON LV

Technical Data:

| Parameters | ASTM | Unit | Typical Results |
|-------------------------------|--------|-------------------|-----------------|
| Viscosity @ 104 °F / 40 °C | D-7042 | cSt | 29.5 |
| Viscosity @ 212 °F / 100 °C | D-7042 | cSt | 6.0 |
| Viscosity Index | D-2270 | | 155 |
| Density @ 60 °F / 15 °C | D-4052 | g/cm ³ | 0.848 |
| Flash Point (min) | D-92 | °C | 208 |
| Pour Point (min) | D-97 | °C | -48 |
| Viscosity Brookfield @ -40 °C | D-2983 | mPa.s (cP) | 12500 |

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. For further Information on Safety Guidelines please refer to MSDS available on our website magicplusoil.net

All statements, information, and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Magic Plus and its affiliates assume legal responsibility.