



ATF TYPE A

MINERAL

Magic Plus ATF TYPE A is a high quality automotive transmission, power steering and hydraulic oil mainly used for heavy duty vehicles. Its special formula enables very smooth operation of torque converters and fluid couplings of automatic transmissions.

Features & Benefits:

- Oxidation and thermal stability
- Dispersancy
- Fircion retention
- Sheer stability
- Anti-wear and EP performance

Applications:

Suitable for use in automatic transmissions of heavy duty vehicles, light duty trucks and passenger vehicles as well as in other power shift transmissions, industrial torque converters, power steering systems and manual transmissions, where a low-viscosity fluid of General Motors Type 'A' Suffix 'A' is specified.

Specifications, Approvals & Recommendations: (Meets / Exceeds)

- GM Type 'A' Suffix 'A'

Technical Data:

Parameters	ASTM	Unit	Typical Results
Viscosity Grade			TYPE A
Viscosity @ 104 °F / 40 °C	D-7042	cSt	52
Viscosity @ 212 °F / 100 °C	D-7042	cSt	7.5
Viscosity Index	D-2270		106
Density @ 60 °F / 15 °C	D-4052	g/cm ³	0.885
Flash Point (min)	D-92	°C	220
Pour Point (min)	D-97	°C	-27

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. For further Information on Safety Guidelines please refer to MSDS available on our website magicplusoil.net

All statements, information, and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Magic Plus and its affiliates assume legal responsibility.