

Power. Speed. Resilience



# DIESEL ENGINE OIL API: CF

# **MINERAL**

Magic Plus API: CF mineral engine oils are formulated for mixed fleet operations. It is blended with an optimized combination of base oil and balanced additive system. Suitable for diesel and naturally aspirated gasoline engines used in trucks and passenger cars operating under harsh driving conditions. This formulation helps provide exceptional thermal stability at high temperatures.

#### Features & Benefits:

- Effective anti-wear properties
- Protection against rust and corrosion
- Effective control over deposits
- Maintains engine cleanliness
- Multigrade benefits
- Good oxidation stability gives longer oil life

## **Applications:**

These heavy duty engine oils are recommended for all types of diesel and gasoline engines where the manufacturer specifies the API service CF.

## Specifications, Approvals & Recommendations: (Meets / Exceeds)

- API: CF/SF
- MB 228.2
- ACEA E2-96, A3/B3
- MAN 270

- Caterpillar TO-2
- MTU Type 1
- Allison C4
- MIL-L-2104-E

### **Technical Data:**

| Parameters                  | ASTM   | Unit     | Typical Results |        |        |        |        |        |        |
|-----------------------------|--------|----------|-----------------|--------|--------|--------|--------|--------|--------|
| Viscosity Grade             |        |          | 15W-40          | 15W-50 | 20W-50 | 20W-60 | SAE 40 | SAE 50 | SAE 60 |
| Viscosity @ 104 °F / 40 °C  | D-7042 | cSt      | 116.4           | 109.5  | 182.75 | 201.05 | 151.4  | 218.85 | 274.9  |
| Viscosity @ 212 °F / 100 °C | D-7042 | cSt      | 15.45           | 15.2   | 20.5   | 24.2   | 15.5   | 20.5   | 24.1   |
| Viscosity Index             | D-2270 |          | 140             | 146    | 132    | 150    | 105    | 110    | 111    |
| Density @ 60 °F / 15 °C     | D-4052 | g/cm³    | 0.882           | 0.878  | 0.891  | 0.887  | 0.895  | 0.896  | 0.897  |
| Flash Point (min)           | D-92   | °C       | 236             | 232    | 236    | 230    | 242    | 246    | 250    |
| Pour Point (min)            | D-97   | °C       | -33             | -33    | -24    | -24    | -15    | -15    | -15    |
| TBN                         | D-2896 | mg KOH/g | 8               | 8      | 8      | 8      | 8      | 8      | 8      |

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. For further Information on Safety Guidelines please refer to MSDS available on our website magicplusoil.net

All statements, information, and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Magic Plus and its affiliates assume legal responsibility.