



MOTOR OIL API: SJ

SEMI SYNTHETIC

Magic Plus API: SJ semi-synthetic motor oil is comprised of high-quality base stocks combined with modern performance additives to help provide long engine life and protect critical engine parts. It helps provide outstanding wear protection under a wide variety of operating conditions.

Features & Benefits:

- Removes sludge from dirty engines
- Superior wear and corrosion protection
- Maintains power and economy by minimizing wear
- Superior viscosity retention
- Oxidation resistant
- Engine Cleanliness and low combustion residue

Applications:

Recommended for gasoline-fueled automobiles and light-duty trucks requiring an API Service Category SJ/CF.

Specifications, Approvals & Recommendations: (Meets / Exceeds)

- API: SJ/CF

Technical Data:

Parameters	ASTM	Unit	Typical Results	
			10W-30	10W-40
Viscosity Grade				
Viscosity @ 104 °F / 40 °C	D-7042	cSt	67.3	90.2
Viscosity @ 212 °F / 100 °C	D-7042	cSt	11.6	15
Viscosity Index	D-2270		169	176
Density @ 60 °F / 15 °C	D-4052	g/cm ³	0.852	0.852
Flash Point (min)	D-92	°C	234	234
Pour Point (min)	D-97	°C	-42	-42
TBN	D-2896	mg KOH/g	6	6

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. For further Information on Safety Guidelines please refer to MSDS available on our website magicplusoil.net

All statements, information, and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Magic Plus and its affiliates assume legal responsibility.