

Power. Speed. Resilience

UTTO (UNIVERSAL TRACTOR TRANSMISSION OIL)

SYNTHETIC

HYDRAULIC / TRANSMISSION

Magic Plus UTTO is an extra high performance multipurpose tractor lubricant engineered to meet or exceed transmission and hydraulic fluid requirements. It is particularly well suited for reducing wet brake and Power Take-Off (PTO) chatter. It helps protect against wear and corrosion of tractor components and has excellent anti friction propertiese. It optimises the performance of agricultural and commercial tractors operating in a wide range of environments and conditions.

Technical Data Sheet

Features & Benefits:

- Ensureseasy gear changing
- High pressure-absorption capability
- Stable to oxidation
- High resistance to aging
- Universal application
- Rationalizes storage
- High wear resistance
- Good cold-start behavior

Specifications, Approvals & Recommendations: (Meets / Exceeds)

- API GL-4
- ALLISON C4
- John Deere J20 A/B/C, J14 B/C
- Massey Ferguson M1135, M1141, M1143, M 1145
- ZF TE-ML-03E, 05F, 06K
- Case MS 1204,6,7,9
- Caterpillar TO-2

Technical Data:

Parameters	ASTM	Unit	Typical Results	
ISO VG Grade			10W-30	5W-30
Viscosity @ 104 °F / 40 °C	D-7042	cSt	72	62.6
Viscosity @ 212 °F / 100 °C	D-7042	cSt	11.6	11.0
Viscosity Index	D-2270		152	170
Density @ 60 °F / 15 °C	D-4052	g/cm³	0.890	0.850
Flash Point (min)	D-92	°C	226	230
Pour Point (min)	D-97	°C	-39	-42

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. For further Information on Safety Guidelines please refer to MSDS available on our website magicplusoil.net

All statements, information, and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Magic Plus and its affiliates assume legal responsibility.

magicplusoil.net 🖂 info@magicplusoil.net 🕼 +971 55 376 4483

Suitable for agricultural machinery in the areas of gearbox, engine, hydraulic systems and immersion brakes for heavy-duty tractors.

- New Holland NH 410B
- Ford / NewHolland FNHA-2-C-201.00
- Ford M2C-48B/C
- Ford M2C-159A
- Ford M2C-86B/C
- Ford M2C-134 A/B/C/D

Applications:

MAGIC